

The system FLUID KEEPER 8 MULTIDISPENSE offers plenty of additional functions compared to the basic version. These are:

- Each control unit allows the monitoring of up to 8 dispensing points and the simultaneous dispense of lubricants in various of them;
- On the connected PC the required measuring unit (liters, gallons, pints, quarts) can quickly be chosen;
- Data entry with a bar code reader (optional) helps to avoid possible errors and to increase operations velocity;
- Wide monitoring of dispensing jobs and dispensing quantities: preset, free or serial mode;
- Management of suppliers: possibility to automatically send emails when predefined minimum levels in lubricants storage tanks have been reached; the operator can send emails to different email addresses and to different suppliers;
- Intuitive graphical interface software.



Art. no. **8876**

Control unit FLUID KEEPER 8 MULTIDISPENSE with alphanumerical keyboard and display. One control unit is necessary per 8 dispensing points and allows also simultaneous dispensing in various dispensing points. There can be installed up to 8 control units in the system.

Art. no. **8877**

Alphanumerical keyboard with display without memory that can be installed optionally and allows to activate any of the connected dispensing points of the system. There can be installed up to 40 of these keyboards in the system.



Art. no. **8879**

Control unit FLUID KEEPER 8 MOBILE with touch screen 7" (185 x 98 mm).



Art. no. **8795**

Bar code reader for FLUID KEEPER 8 MULTIDISPENSE system. Allows to scan all data that can be read by the software. The bar code reader must be connected to an alfanumerical keyboard unit, art. no. 8877. With only one quick transaction all necessary data can be read, avoiding like that any possible errors eventually occurring when entering the data manually on the keyboard.

