

Pneumatic pumps for the supply of low, medium and high viscosity oils and antifreeze for the wall mounted use in pipeworks.



Art. no. **US 2098**



Art. no. **US 2094**



Art. no. **US 2044 Oil**  
Art. no. **US 2047 Pure antifreeze / Waste oil**



Art. no. **US 2064**

Art. no.	<b>US 2044</b>	<b>US 2064</b>	<b>US 2092</b>	<b>US 2093</b>	<b>US 2094</b>	<b>US 2097</b>	<b>US 2098</b>
Compression ratio	1 : 1	3 : 1	7 : 1	4 : 1	6 : 1	10 : 1	1.5 : 1
Compressed air supply	Pressure min 30 psi, max 120 psi						
Outlet pressure	120 psi	350 psi	810 psi	470 psi	700 psi	1450 psi	170 psi
Delivery	9.2 gpm	6 gpm	10 gpm	16 gpm	14.5 gpm	10 gpm	32 gpm
Connection compressed air	1/4" NPT (F)	1/4" NPT (F)	1/2" NPT (F)	1/2" NPT (F)	1/2" NPT (F)	1/2" NPT (F)	1/2" NPT (F)
Connection lubricant outlet	3/4" NPT (M)	1/2" NPT (M)	1" NPT (M)	1" NPT (M)	1" NPT (M)	1" NPT (M)	1" NPT (M)
Max air consumption with 116 psi pressure	55 gpm	55 gpm	507 gpm	507 gpm	475 gpm	475 gpm	507 gpm
Diameter suction tube	Ø 2.17"	Ø 1.58"	Ø 2.17"	Ø 3.15"	Ø 3.15"	Ø 3.15"	Ø 4.33"
Noise level	79 dB	79 dB	79 dB	79 dB	79 dB	78 dB	79 dB
Weight	10 lb	20 lb	33 lb	44 lb	70 lb	50 lb	46 lb