

**1 : 1**  
**12 gpm**

**3 : 1**  
**6.3 gpm**

**5 : 1**  
**4.2 gpm**

**6 : 1**  
**8.5 gpm**

**6 : 1**  
**11 gpm**



Art. no. **US 2040**  
Art. no. **US 2043/L**

Art. no. **US 2020**

Art. no. **US 2025**  
Art. no. **US 2075L**

Art. no. **US 2012**

Art. no. **US 2091**

Art. no.	<b>US 2040</b>	<b>US 2043L</b>	<b>US 2013</b>	<b>US 2020</b>	<b>US 2075L</b>	<b>US 2025</b>	<b>US 2012</b>	<b>US 2091</b>
Compression ratio	1 : 1	1 : 1	2 : 1	3 : 1	5 : 1	5 : 1	6 : 1	6 : 1
Compressed air supply	Pressure min 30 psi, max 120 psi							
Outlet pressure	120 psi	120 psi	240 psi	350 psi	580 psi	580 psi	700 psi	700 psi
Delivery	12 gpm	9 gpm	13 gpm	6.3 gpm	3.4 gpm	4.2 gpm	8.5 gpm	11 gpm
Connection compressed air	1/4" NPT (F)	1/4" NPT (F)	1/2" NPT (F)	1/4" NPT (F)	1/4" NPT (F)	1/4" NPT (F)	1/2" NPT (F)	1/2" NPT (F)
Connection lubricant outlet	3/4" NPT (M)	3/4" NPT (M)	3/4" NPT (M)	1/2" NPT (M)	1/2" NPT (M)	1/2" NPT (M)	3/4" NPT (M)	1" NPT (M)
Max air consumption with 116 psi pressure	55 gpm	55 gpm	69 gpm	55 gpm	69 gpm	69 gpm	69 gpm	518 gpm
Diameter suction tube	Ø 1.10"	Ø 1.10"	Ø 1.10"	Ø 1.10"	Ø 1.10"	Ø 1.10"	Ø 1.30"	Ø 1.10"
Noise level	79 dB	79 dB	79 dB	79 dB	79 dB	79 dB	78 dB	79 dB
Weight	11 lb	11 lb	14 lb	11 lb	11 lb	11 lb	14 lb	13 lb