



AUTOMATIC REWIND, SPRING - DRIVEN HOSE REELS

Standard series Ø max 1/2" - up to 65' length

Ø max 3/8" - up to 80' length



Automatic rewind, spring-driven hose reel, standard series, in painted steel or stainless steel AISI 304, suitable for hoses of max 65' length (Ø hose 1/2") or max 80' length (Ø hose 3/8").

The hose reel can be supplied without hoses or with hoses for the supply of oils, grease, compressed air and water.

On demand the hose reels can also be supplied with a **spring brake kit** (see information at the end of this page).



OPTIONAL
Pivoting wall
mounting bracket



	Art. no.	Art. no. with spring brake	Ø - length hose	P. max	Fluid	Connection threads IN - OUT	Suitable pivoting wall bracket	Dimensions (LxWxH)	Weight (without hose)
Painted steel	US 9016	US 9016/HB	without hose	8700 psi	-	1/2" (M) - 1/2" (F)	Art. no. 9767	98" x 22" x 18"	28.6 lb
	US 9016+3815	US 9016/HB+3815	Ø 3/8" - 50'	300 psi	air - water	1/2" (M) - 3/8" (F)			
	US 9016+28715	US 9016/HB+28715	Ø 1/2" - 50'	2000 psi	oil	1/2" (M) - 1/2" (F)			
	US 9016+4515	US 9016/HB+4515	Ø 1/4" - 50'	6500 psi	grease - water	1/2" (M) - 1/4" (F)	Art. no. 9768	100" x 22" x 18"	40 lb
	US 9021	US 9021/HB	without hose	8700 psi	-	1/2" (M) - 1/2" (F)			
	US 9021+3820	US 9021/HB+3820	Ø 1/2" - 65'	300 psi	air - water	1/2" (M) - 3/8" (F)			
	US 9021+28720	US 9021/HB+28720	Ø 1/2" - 65'	2000 psi	oil	1/2" (M) - 1/2" (F)	Art. no. 9768	100" x 22" x 18"	42 lb
	US 9021+4520	US 9021/HB+4520	Ø 1/4" - 65'	6500 psi	grease - water	1/2" (M) - 1/4" (F)			
	US 9022	US 9022/HB	without hose	8700 psi	-	1/2" (M) - 1/2" (F)			
US 9022+3825	US 9022/HB+3825	Ø 3/8" - 80'	300 psi	air - water	1/2" (M) - 3/8" (F)	Art. no. 9768	100" x 22" x 18"	42 lb	
US 9022+4725	US 9022/HB+4725	Ø 3/8" - 80'	5800 psi	water	1/2" (M) - 3/8" (F)				
US 9022+4525	US 9022/HB+4525	Ø 1/4" - 80'	6500 psi	grease - water	1/2" (M) - 1/4" (F)				
Stainless steel AISI 304	US 9517	US 9517/HB	without hose	2900 psi	-	1/2" (M) - 1/2" (F)	Art. no. 9760	98" x 22" x 18"	28.6 lb
	US 9517+3815	US 9517/HB+3815	Ø 3/8" - 50'	300 psi	air - water	1/2" (M) - 3/8" (F)			
	US 9517+4715	US 9517/HB+4715	Ø 3/8" - 50'	5800 psi	water	1/2" (M) - 3/8" (F)			
	US 9517+4515	US 9517/HB+4515	Ø 1/4" - 50'	6500 psi	grease - water	1/2" (M) - 1/4" (F)	Art. no. 9765	100" x 22" x 18"	40 lb
	US 9522	US 9522/HB	without hose	2900 psi	-	1/2" (M) - 1/2" (F)			
	US 9522+3820	US 9522/HB+3820	Ø 3/8" - 65'	300 psi	air - water	1/2" (M) - 3/8" (F)			
	US 9522+4720	US 9522/HB+4720	Ø 3/8" - 65'	5800 psi	water	1/2" (M) - 3/8" (F)	Art. no. 9765	100" x 22" x 18"	42 lb
	US 9522+4520	US 9522/HB+4520	Ø 1/4" - 65'	6500 psi	grease - water	1/2" (M) - 1/4" (F)			
	US 9521	US 9521/HB	without hose	2900 psi	-	1/2" (M) - 1/2" (F)			
US 9521+3825	US 9521/HB+3825	Ø 3/8" - 80'	300 psi	air - water	1/2" (M) - 3/8" (F)	Art. no. 9765	100" x 22" x 18"	42 lb	
US 9521+4725	US 9521/HB+4725	Ø 3/8" - 80'	5800 psi	water	1/2" (M) - 3/8" (F)				
US 9521+4525	US 9521/HB+4525	Ø 1/4" - 80'	6500 psi	grease - water	1/2" (M) - 1/4" (F)				



/HB Hydraulic spring brake kit

Safety device for the controlled rewind of hoses, installable on all spring-driven hose reel models, eliminating the dangers caused by an uncontrolled rewind or a sudden release of the hose when unwinded during its use.

